

Modulschiene, Typ R-ST, hinten, stabil, Standard, 28 TE

KATALOGNUMMER

34566-528



Combinations of horizontal rails and side panels

	"A" can be combined		"C" combination not recommended	
RAILWAY A		-		RAILWAY B is supported
RAILWAY B		+		RAILWAY C is supported and RAILWAY B is not supported
RAILWAY C		+		-
RAILWAY D		-	-	-
RAILWAY E		-	-	-
RAILWAY F		-	-	-
RAILWAY G		-	-	-
RAILWAY H		-	-	-
RAILWAY I		-	-	-
RAILWAY J		-	-	-
RAILWAY K		-	-	-
RAILWAY L		-	-	-
RAILWAY M		-	-	-
RAILWAY N		-	-	-
RAILWAY O		-	-	-
RAILWAY P		-	-	-
RAILWAY Q		-	-	-
RAILWAY R		-	-	-
RAILWAY S		-	-	-
RAILWAY T		-	-	-
RAILWAY U		-	-	-
RAILWAY V		-	-	-
RAILWAY W		-	-	-
RAILWAY X		-	-	-
RAILWAY Y		-	-	-
RAILWAY Z		-	-	-
RAILWAY AA		-	-	-
RAILWAY AB		-	-	-
RAILWAY AC		-	-	-
RAILWAY AD		-	-	-
RAILWAY AE		-	-	-
RAILWAY AF		-	-	-
RAILWAY AG		-	-	-
RAILWAY AH		-	-	-
RAILWAY AI		-	-	-
RAILWAY AJ		-	-	-
RAILWAY AK		-	-	-
RAILWAY AL		-	-	-
RAILWAY AM		-	-	-
RAILWAY AN		-	-	-
RAILWAY AO		-	-	-
RAILWAY AP		-	-	-
RAILWAY AQ		-	-	-
RAILWAY AR		-	-	-
RAILWAY AS		-	-	-
RAILWAY AT		-	-	-
RAILWAY AU		-	-	-
RAILWAY AV		-	-	-
RAILWAY AW		-	-	-
RAILWAY AX		-	-	-
RAILWAY AY		-	-	-
RAILWAY AZ		-	-	-
RAILWAY BA		-	-	-
RAILWAY BB		-	-	-
RAILWAY BC		-	-	-
RAILWAY BD		-	-	-

Die Modulschiene vom Typ Rugged ST, ermöglicht die isolierte Montage einer Backplane. Die Isolierung erfolgt durch einen Isolierstreifen.

ZERTIFIZIERUNGEN



MERKMALE

Typ R-ST „Rugged“ Modulschiene mit 3-Loch-Befestigung zur Erhöhung der Stabilität

Aluminiumprofil, Oberfläche eloxiert, Kontaktfläche leitfähig, ohne TE-Bedruckung

TE-Bedruckung erfolgt erst ab 28 TE

PRODUKTMERKMALE

Breite Gestell: 28HP

Anzahl Verpackungen: 1

Oberfläche: Eloxiert

Länge: 147.32mm

Material: Aluminium

Produktfamilie: EuropacPRO

Produkttyp: Modulschiene

Typ: Robust, ST

Passt zu: Baugruppenträger

Net Weight: 0.07kg

ZUSÄTZLICHE PRODUKTDDETAILS

Bitte beachten Sie, dass Lieferungen nur in den jeweils angegebenen LLG (Lieferlosgrößen), LLG z. B. 5 Stück, 10 Stück, 50 Stück usw.) möglich sind. Davon abweichende Bestellmengen (z. B. 2 Stück) werden auf die nächst mögliche lieferbare Menge = Lieferlosgröße (LLG) abgeändert.

WARNUNG

nVent-Produkte müssen in Übereinstimmung mit den Produktinformationsblättern und dem Schulungsmaterial von nVent installiert und verwendet werden. Informationsblätter sind verfügbar unter www.nVent.com sowie bei Ihrem nVent-Kundendienstvertreter. Unsachgemäße Installation, Missbrauch, Fehlanwendung oder andere Handlungen im Widerspruch zu den Anweisungen und Warnungen von nVent können zu Fehlfunktionen, Anlagenschäden, schwerer Körperverletzung sowie zum Tod führen und/oder haben die Annullierung der Garantie zur Folge.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Unser starkes markenportfolio:

CADDY

ERICO

HOFFMAN

ILSCO

SCHROFF

TRACHTE