


Guida orizzontale, posteriore, tipo L-MZ, leggera, con guida Z, 40 CV

CODICE A CATALOGO

34560-840



Combinations of horizontal rails and side panels

		+ "A" can be combined		+ combination not recommended		
light 1 A		-	+	+	+	not to be used
heavy 2 B		+	+	not recommended for double the capacity	+	not to be used
light 1 L		+	+	not recommended for double the capacity	+	not to be used
heavy 2 H		not recommended for light	+	+	+	not to be used
channel 2 F		+	+	-	-	not to be used
side panel						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						
channel 2 F						
heavy 2 H						
light 1 L						

La guida orizzontale, tipo leggero con MZ consente l'uso di connettori DIN. I connettori sono conformi alla norma EN 60603-2.

CERTIFICAZIONI



CARATTERISTICHE

Per il montaggio diretto di connettori conformi a EN 60603 (DIN 41612)

Con guida Z per basso carico meccanico (L-MZ)

Alluminio estruso, finitura anodizzata, superficie di contatto conduttiva

ATTRIBUTI DEL PRODOTTO

Larghezza rack: 40HP

Quantità nella confezione: 1

Finitura: Anodizzato

Lunghezza: 208.28mm

Materiale: Alluminio

Famiglia di prodotti: EuropacPRO; RatiopacPRO; RatiopacPRO air; CompacPRO; PropacPRO

Tipo di prodotto: Guida orizzontale

Tipo: Luce, MZ

Funziona con: Rack secondari; Custodie

Gross Weight: 0.071kg

INFORMAZIONI DI PRODOTTO AGGIUNTIVE

La consegna è in confezioni multiple standard. I prezzi si riferiscono a ciascun articolo.

Tenere presente che le consegne possono essere effettuate nei QSP indicati (ad esempio 5 pezzi, 10 pezzi, 50 pezzi, ecc.). Le quantità d'ordine diverse (ad esempio 2 pezzi) possono essere modificate con la quantità di consegna successiva possibile = quantità confezione standard.

AVVERTIMENTO

I prodotti nVent devono essere installati e utilizzati solo come indicato nelle schede istruzioni e nei materiali di formazione di nVent. Le schede istruzioni sono disponibili su www.nvent.com e presso il vostro rappresentante del servizio clienti nVent. Un'installazione scorretta, un uso improprio, un'applicazione errata o qualsiasi altro mancato rispetto completo delle istruzioni e degli avvertimenti di nVent può causare malfunzionamenti del prodotto, danni alla proprietà, gravi lesioni personali e morte e/o annullare la vostra garanzia.

North America

All locations
+1.763.422.2661
Chat with us:
nvent.com/schroff

Europe

Straubenhardt, Germany
+49.7082.794.0
Betschdorf, France
+33.3.88.90.64.90
Warsaw, Poland
+48.22.209.98.35
Assago, Italy
+39.02.932.7141
Chat with us:
nvent.com/schroff

Asia

Shanghai, China
+86.21.2412.6943
Qingdao, China
+86.532.8771.6101
Singapore
+65.6768.5800
Shin-Yokohama, Japan
+81.45.476.0271
Chat with us:
nvent.com/schroff

Middle East & India

Dubai, United Arab
Emirates
+971.4.378.1700
Bangalore, India
+91.80.6715.2001
Istanbul, Turkey
+90.216.250.7374
Chat with us:
nvent.com/schroff



Il nostro straordinario portafoglio di marchi:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE