

Cat HP J-hook, pre-galvanized, 100 mm diameter

Data Solutions

NÚMERO DE CATÁLOGO

CAT64HP



nVent CADDY Cat HP J-Hooks are the foundation of the nVent CADDY Cat HP System. The revamped nVent CADDY Cat HP J-Hook offers contractors three unique, UL-certified attachment methods out of the box—wall, ceiling, and threaded rod installations. This added functionality enables contractors to reduce SKU inventory while maintaining efficiency and continued progress on the jobsite with the most common structural attachment methods.

The modernized design of the nVent CADDY Cat HP J-Hook is engineered to provide optimal support and protection for today's rapidly evolving, high-performing low voltage cable. Contractors can feel confident utilizing the nVent CADDY Cat HP J-Hook due to its installation versatility, superior cable support and protection, and technical certifications.

CERTIFICATIONS



CARACTERÍSTICAS

Versa-Mount Technology: Innovative attachment design provides multiple structural and installation methods for wall, ceiling, and threaded rod mounting applications

Ideal for unknown jobsite applications or attachment methods

Improved design allows for optimized inventory while reducing job site scheduling risks associated with multiple SKUs

Provides optimal support for high-performance data cable—including category cable, Power over Ethernet (PoE), and fiber optic

Industry-leading bend radius designed to protect high-performance data installations

Multiple color options aid in the identification and organization of the pathway application

Provides superior fill capacity and load rating

Compliant with UL® 2043 and suitable for use in air handling (plenum) spaces

Meets ISO®/IEC 14763-2, ANSI®/TIA 568 and ANSI®/TIA 569

Complies with EN 50174-2

CARACTERÍSTICAS DO PRODUTO

Número do artigo: 181064

Material: Aço

Acabamento: Pregalvanized

Diâmetro (Ø): 100mm

Area: 9987mm²

Cable Capacity, Cat 5e: 330

Cable Capacity, Cat 6: 220

Cable Capacity, Cat 6A: 140

Altura 1 (H1): 188.5mm

Altura 2 (H2): 180mm

Static Load: 267N

DETALHES ADICIONAIS DO PRODUTO


Non-continuous supports may not exceed spacing of 5' (1.5 m) per TIA 569-C.9.7 and EN 50174-2.

Cable capacity is calculated based on a 70% fill rate.

Fire Rated Power Cable Capacity (Distance between J-hooks must not exceed 500 mm center to center)												
Part Number		CAT16HP		CAT32HP CAT48HP		CAT64HP		CAT64HP				
Configuration		Single Layer		Single Layer		Single Layer		Double Layer				
Max Load per Support [kg/m]		0.8 kg/m		1.4 kg/m		2.6 kg/m		2 kg/m				
Cable	Linear Weight of the Cable [kg/m]	Number of Cables	Classification	Number of Cables	Classification	Number of Cables		Classification				
4x1,5 (N)HXH FE180 E30-E60	0.234	3	E30	5	E30 E60	11	E30 E60	8	E30 E60			
5x1,5 (N)HXH FE180 E30-E60	0.277	2		5	E30	9	E30	7	E30			
7x1,5 (N)HXH FE180 E30-E60	0.330	2		4		7		6				
12x1,5 (N)HXH FE180 E30-E60	0.513	1		2		5		3				
19x1,5 (N)HXH FE180 E30-E60	0.715	1		1		3		2				
24x1,5 (N)HXH FE180 E30-E60	0.901	-		1		2		2				
30x1,5 (N)HXH FE180 E30-E60	1.052	-		1		2		1				
2x2,5 (N)HXH FE180 E30-E60	0.178	4	E30	-		-		-				
3x2,5 (N)HXH FE180 E30-E60	0.250	3		-		-		-				
4x2,5 (N)HXH FE180 E30-E60	0.296	2		-		-		-				
5x2,5 (N)HXH FE180 E30-E60	0.352	2		-		-		-				
4x1,5 (N)HXH FE180 E90	0.234	3	E30 E60 E90	5	E30 E60 E90	11	E30 E60 E90	8	E30 E60 E90			
5x1,5 (N)HXH FE180 E90	0.277	2		5		9		7				
7x1,5 (N)HXH FE180 E90	0.330	2		4		7		6				
12x1,5 (N)HXH FE180 E90	0.511	1		2		5		3				
24x1,5 (N)HXH FE180 E90	0.901	-		1		2		2				
2x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.060	13	E30	-		-		-				
4x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.102	7		-		-		-				
8x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.221	3		-		-		-				
12x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.281	2		-		-		-				
16x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.326	2		-		-		-				
20x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.421	1		-		-		-				

32x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.588	1	-	-	-
40x2x0,8 JE-H(St)H...Bd FE180 E30-E90	0.761	1	-	-	-
Fire rating applicable when linking specified J-hook to the following components		Fire rating applicable to the following riveted assemblies			
Part number		Part number			
CATHPAN		CAT16HPAB	CAT32HPAB	CAT48HPAB	CAT64HPAB
CATHPA4		CAT16HPBCB	CAT32HPAFAB3	CAT48HPAFAB3	CAT64HPAFAB3
CATHPA6		CAT16HPBC200B	CAT32HPAFAB4	CAT48HPAFAB4	CAT64HPAFAB4
CATHPTM		CAT16HP24SM	CAT32HPAFAB6	CAT48HPBCB	CAT64HPBCB
CATHPBCB		CAT16HP58SM	CAT32HPBCB	CAT48HP58SM	CAT64HPBC200B
CATHPBC200B		CAT16HP912SM	CAT32HPBC200B	CAT48HP912SM	CAT64HP58SM
CATHP912SM		CAT16HP24	CAT32HP24SM	CAT48HP24	CAT64HP912SM
CATHP24		CAT16HP58	CAT32HP912SM	CAT48HP58	CAT64HP24
CATHP58		-	CAT32HP24	-	-
CATHP912		-	-	-	-

DIAGRAMAS



AVISO

Os produtos nVent devem ser instalados e utilizados apenas conforme indicado nas fichas de instrução do produto e materiais de treinamento da nVent. As fichas de instrução estão disponíveis em www.nVent.com e com nossos representantes de atendimento ao cliente nVent. A instalação inadequada, uso incorreto, aplicação incorreta ou outra falha qualquer em seguir completamente as instruções e avisos da nVent podem levar ao mau funcionamento do produto, danos à propriedade, lesões corporais graves e morte, e/ou anular sua garantia.



O nosso forte portfólio de marcas:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE